
QSC MP-M40



010181_mp_m40_01_opt.jpg



?????? ?? 8 ?????????? ??? 6 ?????????.

?????????????: ??? ?????????????? ?????
????? ??????????
???????? ????? ?? ??? 1643,00 €

????? ????????? 1643,00 €

?????????? ?????? 318,00 €

[?????? ? ? ?](#)

?????????QSC

???????

??????????:

- ??????: 8
Mic/Line: 4 (Euroblock)
RCA: 4 (mono-summed RCA pairs)
- ?????: 6
Line: 4 (Euroblock, balanced)
Music on Hold: 1 (Euroblock, transformer balanced)
Cue (phones): 1 (3.5 mm, stereo)
- Input Processing: EQ 4-band parametric EQ with high/low shelving option, variable 24/octave HPF and LPF, Dynamics Gate, choice of Auto Gain Control (AGC) or Compressor
- Output Processing: EQ 1/3 octave GEQ, Anti-feedback Filters 12-band variable notch filters, Dynamics Comp/limiter, ducker, loudness. Delay 100 msec
- Loudspeaker tunings: Factory: Intrinsic Correction™ voicing for QSC loudspeakers, User: 6-band parametric EQ, HPF & LPF (Linkwitz-Riley or Butterworth; 12, 18 or 24 dB/octave)
- Effects & RTA: Effects 1 multi-effects processor, RTA 1/3 octave RTA
- ????? ?????: Ethernet 1 x RJ45 for connection to Wi-Fi router (user supplied), MP-MFC ports 2 x RJ45, GPI 2 Inputs (Euroblock)
- ??????????: MP-MFC Optional wall controller, MP Install app For configuration/design functions (for iOS/Android tablets, Windows and Mac OS PCs), MP Manage app For end user control functions (for iOS/Android tablets and smartphones)
- Phantom Power: All microphone inputs (+12 volts)
- Power Requirements: TBD W, 100-240 VAC, 50-60 Hz, universal supply, IEC inlet
- Indicators: Blue POWER LED, blue STATUS LED
- ??????: 4.5 cm X 48.3 cm X 35.6 cm
- ?????: 3.2 kg