

## Metro Audio Systems

- ? . ??????? - ? . ??????? ??  
????????? 18  
15124 ???????  
??????  
??????  
+302106129821  
+302103471044  
?????????

---

## QSC AD-C.SUB 6.5" BLACK



010222\_ad\_c\_sub\_blk\_01\_opt.jpg

# Metro Audio Systems

- ? . ??????? - ? . ??????? ??  
????????? 18  
15124 ???????  
??????  
??????  
+302106129821  
+302103471044  
?????????

---



# Metro Audio Systems

- ? . ??????? - ? . ??????? ??  
???????? 18  
15124 ??????  
?????  
?????  
+302106129821  
+302103471044  
????????

---



???????????? subwoofer ????? 6,5", ????? 100W /20V  
~~??~~  
???????????? 532,00 €  
???????????? 532,00 €  
???????????????? 102,97 €

 ΔΙΑΘΕΣΙΜΟ ΣΕ 7+ ΜΕΡΕΣ

[???????? ? ? ? ? ? ? ? ?](#)  
[?????????????????QSC](#)

?????????????????:

- LF transducer: 6.5" (165 mm) dual voice-coil weather treated paper cone woofer
- Effective frequency range 45 Hz – 150 Hz
- Rated noise power / voltage 100 W / 20 V (rms)
- Sensitivity [dB]: (rated @ 1 W, 1 m) 86
- Maximum SPL [dB]: (continuous / peak) 100 / 106
- Recommended amplifier: 100 W
- Transformer taps / impedance
- Bypass: 4 ?
- 100 W (70 V); NA (100 V) Tap: 50 ?
- 50 W (70 V); 100 W (100 V) Tap: 100 ?
- 25 W (70 V); 50 W (100 V) Tap: 200 ?
- 12.5 W (70 V); 25 W (100 V) Tap: 400 ?
- Connectors: Mono input: 4-pole Euroblock with thru output
- Hi-pass mono output: 2x 4-pole Euroblock for 4x satellites
- Enclosure material: ABS baffle on powder coated steel back can
- Grill material Powder coated steel
- Ingress protection: IP-34
- Operating environment: Designed for indoor use
- Operating temperature range: -4 to 122° F (-20 to 50° C)
- ?????: 8.7 kg
- ??????????: O 340 x 254 mm