
Allen & Heath dLive DM32



144.793_mixrack_dm32_01_opt.jpg



32 mic/line inputs. 16 line outputs

?????????: ??? ?????????? ????
???? ???????

ΚΑΤΟΙΝ ΠΑΡΑΓΓΕΛΙΑΣ

[??????? ??? ?? ??????](#)

????????????[ALLEN-HEATH](#)

?????????

- 32 mic/line inputs, 16 line outputs
- XCVI 160x64 FPGA core
 - 96kHz sample rate
 - Variable bit-depth for ultimate precision and noise performance
 - Virtually infinite mix headroom thanks to 96bit accumulator
 - Class leading, ultra-low latency < 0.7ms
- 128 Input Channels with full processing
- 64 Mix Outputs with full processing
- Configurable 64 bus architecture (group, FX, aux, matrix, mains)
 - LR, LCR and up to 5.1 mains mode
 - Multiple PFLs
- 16 RackExtra FX with dedicated stereo returns
- 16 DCAs
- AMM (Automatic Mic Mixer) up to 64 channels across 1, 2 or 4 zones
- Built-in signal generator and RTA
- New preamp design for extra transparency
- Unique Active PAD circuit for consistent performance with any source
- Connection hub
 - Dual redundant GigaACE gigabit link to Surface
 - 2x redundant DX links for I/O expansion
 - 3x I/O Ports – 128 ch 96 kHz each
 - Dedicated ME-1 48kHz port
 - 2x Network ports
 - Wordclock BNC I/O
- Add up to 46 DX I/O expanders via DX Hub modules or DX Link cards
- Dual redundant, hot swappable power supply
- Flush front panel with ultra quiet fan
- Reversible rack ears design
- 3 Year Warranty