

QSC AD-C.SUB White



????????????? subwoofer ?????? 6,5", ?????? 100W /20V

?????????: ?? ?????????? ??????
???? ??????
????? ??? ? ? 632,40 €

??? ?????? 632,40 €

??????? ????? 122,40 €

 ΚΑΤΟΠΙΝ ΠΑΡΑΓΓΕΛΙΑΣ

[??????? ?? ? ??????](#)

?????????????QSC

?????????

?????????????:

- LF transducer: 6.5" (165 mm) dual voice-coil weather treated paper cone woofer
- Effective frequency range 45 Hz – 150 Hz
- Rated noise power / voltage 100 W / 20 V (rms)
- Sensitivity [dB]: (rated @ 1 W, 1 m) 86
- Maximum SPL [dB]: (continuous / peak) 100 / 106
- Recommended amplifier: 100 W
- Transformer taps / impedance
- Bypass: 4 ?
- 100 W (70 V); NA (100 V) Tap: 50 ?
- 50 W (70 V); 100 W (100 V) Tap: 100 ?
- 25 W (70 V); 50 W (100 V) Tap: 200 ?
- 12.5 W (70 V); 25 W (100 V) Tap: 400 ?
- Connectors: Mono input: 4-pole Euroblock with thru output
- Hi-pass mono output: 2x 4-pole Euroblock for 4x satellites
- Enclosure material: ABS baffle on powder coated steel back can
- Grill material Powder coated steel
- Ingress protection: IP-34
- Operating environment: Designed for indoor use
- Operating temperature range: -4 to 122° F (-20 to 50° C)
- ?????: 8.7 kg
- ?????????: 340 x 254 mm