QSC AD-P.SUB White



010231_ad_p_sub_wht_01_opt.jpg



-????????????? subwoofer 6,5" -?????? 100W /20V

??????????: ??? ???????????? ?????
???? ???????
?????? ???? ?? ??? 669,60 €

???? ??????? 669,60 €

???????? ????? 129,60 €

ΚΑΤΟΠΙΝ ΠΑΡΑΓΓΕΛΙΑΣ

??????? ??? ?? ??????

?????????????QSC

?????????

??????????????:

- LF transducer: 6.5" (165 mm) dual voice-coil weather treated paper cone woofer
- Effective frequency range 55Hz – 150 Hz
- Rated noise power / voltage 100 W / 20 V (rms)
- Sensitivity [dB]: (rated @ 1 W, 1 m) 86
- Coverage (-6 dB): Omni
- Maximum SPL [dB]: (continuous / peak) 100 / 106
- Recommended amplifier: 100 W
- Transformer taps / impedance:
  Bypass:4 ?
  100 W (70 V); NA (100 V) Tap: 50 ?
  50 W (70 V); 100 W (100 V) Tap: 100 ?
  25 W (70 V); 50 W (100 V) Tap: 200 ?
  12.5 W (70 V); 25 W (100 V) Tap: 400 ?
- Connectors: Mono input: Hi-Z mono input: 4-pole Euroblock with thru output, Hi-pass mono output: x2 4-Pole Euroblock for x4 satellites
- Enclosure material: ABS
- Grille material: Powder coated steel
- Ingress protection: IP-34
- Operating environment: Designed for indoor use
- Operating temperature range: -4 to 122° F (-20 to 50° C)
- ?????: 7.5 kg
- ?????????: O 4.3 x 4.5mm